

CERMIFILM

SYNTHETIC RESIN BASED, READY TO USE PRIMER



Pink

- *Increasing adhesion to surfaces*
- *Prevents dusting on surfaces*
- *Ready to use*

- *Balancing the water absorbency of surfaces*
- *Solvent-free and odorless*



PRODUCT INFORMATION

WHERE TO USE

- Increasing the adhesion strength of cement-based products to be applied by balancing the water absorbency of surfaces such as plaster, concrete, plaster, screed etc.
- Especially before ceramic tile coating, leveling screed, waterproofing, paint applications;
- It is used to prevent problems such as poor adhesion, cracking, peeling etc. by absorbing water quickly.

GENERAL FEATURES

Material structure : Liquid containing synthetic resin
Appearance : Liquid
Colour : Pink
Density : $1.0 \pm 0.1 \text{ gr/cm}^3$
 (ASTM D1475 DIN 53217 ISO 2811)

TECHNICAL CHARACTERISTICS

Moisture Resistance : Good
Resistance to Heat Aging : Perfect
Flexibility : Good
Acid and Alkali Resistance : Medium

(*). These values are obtained as a result of laboratory tests and are the performance values of the finished applications after 28 days. Values may vary due to differences in the construction site environment.

STANDARDS AND DOCUMENTS

- Public Works ; 04.466/3

CONSUMPTION

- Average : 0.100-0.150 lt/m²

PACKAGING

- 5 lt plastic drums

STORAGE

- Moisture-free, dry and protected against external weather conditions should be stocked in warehouses.
- Shelf life is 1 year under appropriate storage conditions.
- Opened packages should be kept tightly closed.



Interior -
Exterior



Surface
Inspection



Application
Temperature



Application with
Brush-Roller



SOLVENT-
FREE

APPLICATION

APPLICATION PROCEDURE

Application Temperature: +5 °C - +35 °C

Drying Time: 45-60 min

SUBSTRATE PREPARATION

- Surfaces must be cured, sound, clean, dust-free, free of mold oils and other foreign materials.
- In extremely hot summer months, the ground should be slightly moistened by sprinkling water before application.
- Defects, cracks and holes on the application surface corrected properly with repair mortars **CERMIMORTAR** or **CERMIREP R3 T** and **CERMIREP R4 T** and must be repaired.



APPLICATION

- **CERMIFILM** is thoroughly mixed before application and applied to the surface with a brush or roller in a saturated manner without thinning.
- After 1 hour drying time, other applications such as waterproofing, ceramic etc. can be started. This period may be longer in cold and humid weather.
- Since it is difficult to clean, care should be taken to apply without splashing during application in order not to contaminate the surface.

RECOMMENDATIONS

- No water or other additives should be added.
- **CERMIFILM** primer applied to the surface should not be kept under the sun for a long time.
- It should not be used on water repellent surfaces and ceramic on ceramic applications.
- The surface should not be exposed to water after application.
- Do not apply in areas that are frozen or at risk of freezing.

SAFETY INSTRUCTIONS

- Do not inhale, avoid contact with skin and eyes.
- It is recommended to use appropriate work equipment (gloves, goggles, mask, knee pads, etc.) during product application.
- For more detailed information read the Product Safety Data Sheet (MSDS).

Note: Technical values and application instructions are valid under ambient temperature of 23°C with relative humidity 50% and they are the results of our tests and experience in accordance with international standards. Our company is not responsible for any errors that may occur if the instructions and recommendations specified in the technical data sheets are not followed.

CERMIX

CERMIX Produced by Koramic Yapı Kimyasalları under license of Cermix SA. www.cermix.com.tr * www.koramic.com.tr

Head Office
Koramic Yapı Kimyasalları San. Tic. A.Ş.
E-5 Karayolu Üzeri, Sıfı Mah. Hükümet Cad.
Tuzla 34941 İstanbul / TÜRKİYE
Phone: +90.216.423 34 33 • Fax: +90.216.423 53 63

Bozüyük Factory
Bozüyük Organize San. Böl. 10. Cad.
106 Ada / 5 Parsel No: 3 Bozüyük - BİLEÇİK / TÜRKİYE
Phone: +90.228.314 63 00
Fax: +90.228.314 63 0

Tarsus Factory
Huzurkent Tarsus Organize Sanayi Bölgesi
13. Cadde No: 10 Tarsus - MERSİN / TÜRKİYE
Phone: +90.324.676 40 41-676 42 32-676 44 49
Fax: +90.324.676 40 47