

CERMIMIX



WATER IMPERMEABILITY ADMIXTURE FOR CEMENT BASED MORTAR AND CONCRETE



Brown

- *Increases water impermeability in mortar and concrete*
- *Increases the strength of the mortar*
- *Not affected by lime*
- *Protects the reinforcement in the concrete structure against corrosion*
- *Ready to use*
- *Does not cause any change in setting and curing times*

PRODUCT INFORMATION

WHERE TO USE

- Increasing the water impermeability of concrete, mortar, plaster and screeds,
- Especially in concrete of water tanks, swimming pools, foundations and curtains etc,
- It is used to close pores and cracks at the capillary level.

GENERAL FEATURES

Density	: $0,95 \pm 0,1\text{gr/cm}^3$
Appearance	: Liquid
Content	: Sodium lignosulfonate mixture
pH	: 10 ± 1
Color	: Brown

CONSUMPTION


- In addition to the mortar mixture,
 - 1 Units Cermimix: 10 Units Water (*)
- (*) If the sand used is moist, this ratio should be 1:8 or 1:6.

PACKAGING

- 5 lt plastic drums
- 20 lt plastic drums

STORAGE

- Moisture-free, dry and protected against external weather conditions should be stocked in warehouses.
- Shelf life is 1 year under appropriate storage conditions.
- Opened packages should be kept tightly closed.



APPLICATION

APPLICATION PROCEDURE

- Shake **CERMIMIX** well before use.
- The product is used by adding to clean water.
- Add the appropriate amount of **CERMIMIX** to the consistency of the mortar. Increases the water impermeability performance of cement based mortars and concretes when used as an admixture.
- Trial mixtures should be made to determine dosage rates and water requirements.

RECOMMENDATIONS

- Application should not be made on hot surfaces exposed to excessive wind or direct sunlight, if it is necessary to apply in these environments, the environment and surface should be prepared for application before starting.
- Do not apply in rainy weather, the application surface should be protected from rain for 24 hours.
- The expired and crusted product in the container should not be used.
- It is important to have homogeneous distribution in the mortar.
- For full performance, the mortar or concrete in which it is added should be allowed to cure.
- Please contact our technical service for other applications.

SAFETY INSRUCTIONS

- Do not inhale, avoid contact with skin and eyes.
- It is recommended to use appropriate work equipment (gloves, goggles, mask, knee pads, etc.) during product application.
- For more detailed information read the Product Safety Data Sheet (MSDS).

Note: Technical values and application instructions are valid under ambient temperature of 23°C with relative humidity 50% and they are the results of our tests and experience in accordance with international standards. Our company is not responsible for any errors that may occur if the instructions and recommendations specified in the technical data sheets are not followed.

CERMIMIX

CERMIX Produced by Koramic Yapı Kimyasalları under license of Cermix SA. www.cermix.com.tr * www.koramic.com.tr

Head Office
Koramic Yapı Kimyasalları San. Tic. A.Ş.
E-5 Karayolu Üzeri, Şifa Mah. Hükümet Cad.
Tuzla 34941 İstanbul / TÜRKİYE
Phone: +90.216.423 34 33 • Fax: +90.216.423 53 63

Bozüyük Factory
Bozüyük Organize San. Böl. 10. Cad.
106 Ada / 5 Parsel No: 3 Bozüyük - BİLEÇİK / TÜRKİYE
Phone: +90.228.314 63 00
Fax: +90.228.314 63 0

Tarsus Factory
Huzurkent Tarsus Organize Sanayi Bölgesi
13. Cadde No: 10 Tarsus - MERSİN / TÜRKİYE
Phone: +90.324.676 40 41-676 42 32-676 44 49
Fax: +90.324.676 40 47