

# CERMISEP KA

## MINERAL OIL BASED MOLD RELEASE AGENT



White



- Ready to use
- Allows the mold to be separated from the concrete more easily
- Easy to apply

- Extending the service life of the mold
- Ensuring smooth surface concrete
- Reduces air bubbles on the surface of concrete.

## PRODUCT INFORMATION

### WHERE TO USE

• It is used in cases where it is desired to increase mold efficiency in Wood, steel, plastic, ply-wood molds and to accelerate mold workmanship.

### GENERAL FEATURES

<b>Structure</b>	: Emulsified Mineral Oil
<b>Color</b>	: White
<b>Density</b>	: 0.97 +- 0.02 kg/L

### STANDARDS AND DOCUMENTS

- Public Works pos. no. 04.116/1

### CONSUMPTION

• It varies depending on the type of mold and the roughness of its surface. Approximately 9 to 19 m<sup>2</sup> of mold surface can be greased with 1 kg of **CERMISEP KA**.




### PACKAGING

- 20 kg plastic drum

### STORAGE

- It should be stored in moisture-free, dry and protected against external weather conditions.
- Shelf life is 1 year under appropriate storage conditions.
- Opened packages should be kept tightly closed.



## APPLICATION

### APPLICATION PROCEDURE

**Application temperature :** +5°C, +40°C

### SUBSTRATE PREPARATION

• Before using **CERMISEP KA**, the molds must be dry, clean and free of concrete and rust residues.

### APPLICATION


- **CERMISEP KA** is ready for use and must be mixed before use.
- It can be applied to the clean mold surface with a roller, brush oakum or pulverizer.
- For maximum performance, the product should be applied homogeneously and thinly.
- Discharges and excess fluids should be removed with a oakum.
- Very absorbent and old molds may require a 2nd coat.

### RECOMMENDATIONS

- Water should not be added before and after use.

### SAFETY INSTRUCTIONS

- Do not inhale, avoid contact with skin and eyes.
- It is recommended to use appropriate work equipment (gloves, goggles, mask, knee pads, etc.) during product application.
- The risk of flammability is low due to the high flash point. However, adequate ventilation must be provided in the environment, and open flames should not be brought near the area during use.
- For more detailed information please read the Material Safety Data Sheet (MSDS).



**Note:** Technical values and application instructions are valid under ambient temperature of 23°C with relative humidity 50% and they are the results of our tests and experience in accordance with international standards. Our company is not responsible for any errors that may occur if the instructions and recommendations specified in the technical data sheets are not followed.

**CERMIX**

CERMIX Produced by Koramic Yapı Kimyasalları under license of Cermix SA. [www.cermix.com.tr](http://www.cermix.com.tr) \* [www.koramic.com.tr](http://www.koramic.com.tr)

Head Office  
Koramic Yapı Kimyasalları San. Tic. A.Ş.  
E-5 Karayolu Üzeri, Şifa Mah. Hükümet Cad.  
Tuzla 34941 İstanbul / TÜRKİYE  
Phone: +90.216.423 34 33 • Fax: +90.216.423 53 63

Bozüyük Factory  
Bozüyük Organize San. Böl. 10. Cad.  
106 Ada / 5 Parsel No: 3 Bozüyük - BİLEÇİK / TÜRKİYE  
Phone: +90.228.314 63 00  
Fax: +90.228.314 63 0

Tarsus Factory  
Huzurkent Tarsus Organize Sanayi Bölgesi  
13. Cadde No: 10 Tarsus - MERSİN / TÜRKİYE  
Phone: +90.324.676 40 41-676 42 32-676 44 49  
Fax: +90.324.676 40 47