

DECLARATION OF PERFORMANCE

Manufacturer	KORAMIC YAPI KİMYASALLARI SANAYİ TİCARET ANONİM ŞİRKETİ
Contact Information	Bozüyük OSB 10. Cadde No: 7 Bozüyük, Bilecik – Turkey info@koramic.com.tr
Registered Trademarks	Cermifloor 4-30
Unique Product Identification Codes	CT, F10, C25
Intended Use	Cement based, rapid setting, fiber reinforced, self leveling surface smoothing mortar.
Related Directive	305/2011/EU Construction Materials Regulations
Harmonized Standard	TS EN 13813: Jan 2004
System of Constancy of Performance	SYSTEM 3 ; SYSTEM 3 FOR REACTION TO FIRE

Declaration of Performance		
Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class A1	TS EN 13501-1:2019
Flexural Strength	≥ 10 N/mm ²	TS EN 13892-2:2004
Compressive Strength	≥ 25 N/mm ²	TS EN 13892-2:2004

We hereby declare and engage that; the stated product and models are produced as covering the requirements of the related directives and harmonized standards and in conformity with the declared performance. We performed the obligations under System 3 and issued this declaration due to the reaction to fire test report (Era-21-007) provided by Efectis Era (NB2184). This declaration and performance do not provide guarantee right about the product and its features and the conformity, which is under sole responsibility of the manufacturer, is valid as long as terms of use are followed.

CE-CSL-02
03.03.2021



Feyza ÇALI
R&D Manager