

CERMIFILM PLUS



**SYNTHETIC RESIN BASED, READY TO USE,
FILLED PRIMER FOR GLOSSY SURFACES**



Blue

- *Ideal for ceramic applications over old ceramic*
- *Prevents dusting on surfaces*

- *Solvent-free and odorless*
- *Ready to use*

PRODUCT INFORMATION

WHERE TO USE

- Increasing adhesion strength on smooth and non-absorbent surfaces thanks to its special filled structure,
- Before application on absorbent surfaces such as gypsum concrete, plaster, screed etc,
- It is especially used before ceramic application on old ceramics, marble glass etc.

GENERAL FEATURES

Material structure : Synthetic resin based and mineral filler
Type : Liquid
Colour : Blue
Density : $1.6 \pm 0.1 \text{ gr/cm}^3$
 (ASTM D1475 DIN 53217 ISO 2811)

TECHNICAL CHARACTERISTICS

Moisture Resistance : Good
Resistance to Heat Aging : Perfect
Flexibility Acid and Alkali Resistance : Medium

STANDARDS AND DOCUMENTS

- Public Works POS. 10.300.1171

CONSUMPTION

- Average: 0.300-0.400 kg/m²




PACKAGING

- 10 kg plastic bucket
- 5 kg plastic bucket
- 3 kg plastic bucket
- 1 kg plastic bucket

STORAGE

- Moisture-free, dry and protected against external weather conditions should be stocked in warehouses.
- Shelf life is 1 year under appropriate storage conditions.
- Opened packages should be kept tightly closed.



APPLICATION

APPLICATION PROCEDURE

Application Temperature: +5 °C - +35 °C

Drying Time: Min. 60 min

Waiting Time After Application: 1 hour

CERMIFILM PLUS is ready to use and can be applied to the surface with a brush or roller.

SUBSTRATE PREPARATION

- Surfaces must be cured, sound, clean, dust-free, free of mold oils and other foreign materials.
- Defects, cracks and holes on the application surface corrected properly with repair mortars **CERMIMORTAR** or **CERMIREP R3 T** and **CERMIREP R4 T** and must be repaired.

APPLICATION

- **CERMIFILM PLUS** is ready to use, thoroughly mixed before application, and applied to the surface with a brush or roller in a saturated manner.
- After 1 hour drying time, other applications can be started. This period may be longer in cold and humid weather.
- Since it is difficult to clean, care should be taken not to splash during application in order not to contaminate the surface.

RECOMMENDATIONS

- No water or other additives should be added.
- **CERMIFILM PLUS** primer applied to the surface should not be kept under the sun for a long time.
- Do not apply on wet and damp surfaces.
- The surface should not be exposed to water after application.
- Do not apply in areas that are frozen or at risk of freezing.

SAFETY INSTRUCTIONS

- Do not inhale, avoid contact with skin and eyes.
- It is recommended to use appropriate work equipment (gloves, goggles, mask, knee pads, etc.) during product application.
- For more detailed information read the Product Safety Data Sheet (MSDS).



Note: Technical values and application instructions are valid under ambient temperature of 23°C with relative humidity 50% and they are the results of our tests and experience in accordance with international standards. Our company is not responsible for any errors that may occur if the instructions and recommendations specified in the technical data sheets are not followed.

CERMIX

CERMIX Produced by Koramic Yapı Kimyasalları under license of Cermix SA. www.cermix.com.tr * www.koramic.com.tr

Head Office
Koramic Yapı Kimyasalları San. Tic. A.Ş.
E-5 Karayolu Üzeri, Şifa Mah. Hükümet Cad.
Tuzla 34941 İstanbul / TÜRKİYE
Phone: +90.216.423 34 33 • Fax: +90.216.423 53 63

Bozüyük Factory
Bozüyük Organize San. Böl. 10. Cad.
106 Ada / 5 Parsel No: 3 Bozüyük - BİLEÇİK / TÜRKİYE
Phone: +90.228.314 63 00
Fax: +90.228.314 63 0

Tarsus Factory
Huzurkent Tarsus Organize Sanayi Bölgesi
13. Cadde No: 10 Tarsus - MERSİN / TÜRKİYE
Phone: +90.324.676 40 41-676 42 32-676 44 49
Fax: +90.324.676 40 47